

30 HP Enclosed Rotary Screw



77 dBA

125 cfm @ 150 psi

130 cfm @ 125 psi

Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation

CDR Compressor Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines
- Vibration isolation pads
- Free freight in the 48 states & southern Canada



Model Number	Phase	Voltage	Tank	Package	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
RS303ENC	3	208-230-460	N/A	Basic	42	43	59	72	36
RS303ENC-CRD	3	208-230-460	120 Gallon Vertical	CRD	42	43	59	72	36

No Start Up Kit Required

Optional 5-year Pump Warranty Available

See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 5-2019

