#### ALWAYS MAKE SURE POWER IS OFF TO COMPRESSOR AND CONTACT FACTORY AUTHORIZED SERVICE CENTER OR FACTORY FOR ADVICE

## Pressure Switch Adjustment Furnas Style NNTOSSOD AIT SVS(()

972-352-6304/800-531-9656





## **Pressure Switch**

Before adjusting pressure switch make contact factory to make sure setting will not over amp compressor drive motor

# MAKE SURE POWER TO COMPRESSOR IS OFF BEFORE WORKING ON PRESURE SWITCH

www.compressed-air-systems.com



## Pressure Switch Adjustment Furnas Style NGSSON AIR SYS



972-352-6304/800-531-9656



Remove hold down screw from pressure switch cover



Pressure adjustment screw (brass colored) only adjust this screw

DO NOT ADJUST OR TAMPER
WITH BLACK PLASTIC SCREW

### ALWAYS MAKE SURE POWER IS OFF TO COMPRESSOR AND CONTACT FACTORY AUTHORIZED SERVICE CENTER OR FACTORY FOR ADVICE



## Pressure Switch Adjustment Furnas Style NAME TITE BOSSOUL



972-352-6304/800-531-9656



Adjust pressure set screw ¼ turn down to raise pressure or ¼ turn up to lower pressure (Do not adjust more than ¼ turn with out checking to see what the new operating pressure of the compressor is)



tighten hold down screw Put cover back on pressure switch and