

15 HP Open Rotary Screw

68 CFM @ 125 PSI
55 CFM @ 150 PSI
77 DBA

Basic Compressor

Features

- Airend manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL Control components
- Omega profile rotors
- Air/Oil cooler
- Easy to remove bolt on oil cooler for cleaning
- Operating pressures from 100-190 PSI available
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- Factory filled with premium synthetic fluid
- ASME Powder coated air receiver
- Heavy duty air filter

Elite Compressor

Features

- All basic features
- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Free freight in the 48 states & southern Canada



| Model Number | Phase | Voltage | Tank | Elite/Basic | Length | Width | Height | Amp Draw 230 Volt | Amp Draw 480 Volt |
|--------------|-------|-------------|-----------------------|-------------|--------|-------|--------|----------------------|----------------------|
| RS153H120 | 3 | 208-230-460 | 120 Gallon Horizontal | Basic | 72 | 28 | 45 | 42 | 21 |
| RS153H120-E | 3 | 208-230-460 | 120 Gallon Horizontal | Elite | 72 | 28 | 45 | 42 | 21 |

No Start Up Kit Required

See catalog for additional options



Compressed Air Systems

Simplicity. It's What We Do

www.compressed-air-systems.com

