

25 HP Open Rotary Screw

108 CFM @ 125 PSI
102 CFM @ 150 PSI

Basic Compressor

Features

- Airend manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL Control components
- Omega profile rotors
- Air/Oil cooler
- Easy to remove bolt on oil cooler for cleaning
- Operating pressures from 100-190 PSI available
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- Factory filled with premium synthetic fluid
- ASME Powder coated air receiver
- Heavt duty air filter

Elite Compressor

Features

- All basic features
- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Free freight in the 48 states & southern Canada



Model Number	Phase	Voltage	Tank	Elite/Basic	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
RS253H120	3	208-230-460	120 Gallon Horizontal	Basic	72	36	54	63	32
RS253H120-E	3	208-230-460	120 Gallon Horizontal	Elite	72	36	54	63	32

No Start Up Kit Required

See catalog for additional options



Compressed Air Systems

Simplicity. It's What We Do

www.compressed-air-systems.com

