


40-125 CFM Hydraulic Driven Reciprocating

40 CFM @ 150 PSI
60 CFM @ 150 PSI
125 CFM @ 150 PSI

Basic Features

- Airend manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Single solenoid operation
- UL control components
- Omega profile rotors
- Easy to remove bolt on compressor oil cooler
- Operating pressures from 100-190 PSI
- Heavy duty air filter
- Factory filled with premium synthetic fluid
- Standard steel cover



Elite Features

- All basic features
- Air/Oil Cooler
- Aluminum diamond plate cover
- Vibration isolation pads
- Freight pre-paid in the 48 states & southern Canada



Model	CFM	PSI	Elite/Basic	Length	Width	Height	GPM	PSI
H-BM40RS	40	150	Basic	32	19	24	10	2850
H-BM40RS-E	40	150	Elite	32	19	24	10	2850
H-BM60	60	150	Basic	32	21	26	15	2850
H-BM60-E	60	150	Elite	32	21	26	15	2850
H-BM125	125	150	Basic	40	27	34	30	2850
H-BM125-E	125	150	Elite	40	27	34	30	2850

No Start Up Kit Required

See catalog for additional options



Compressed Air Systems

Simplicity. It's What We Do

www.compressed-air-systems.com

