

5 HP Open Rotary Screw

19 CFM @ 125 PSI
16 CFM @ 150 PSI
74 DBA

Basic Compressor

Features

- Airend manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL Control components
- Omega profile rotors
- Air/Oil cooler
- Easy to remove bolt on oil cooler for cleaning
- Operating pressures from 100-190 PSI available
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- Factory filled with premium synthetic fluid
- ASME Powder coated air receiver
- Heavy duty air filter

Elite Compressor

Features

- All basic features
- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Free freight in the 48 states & southern Canada



Model Number	Phase	Voltage	Tank	Elite/Basic	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
RS51V80	1	208-230	80 Gallon Vertical	Basic	32	24	76	24	N/A
RS53V80	3	208-230-460	80 Gallon Vertical	Basic	32	24	76	16	8
RS51V80-E	1	208-230	80 Gallon Vertical	Elite	32	24	76	24	N/A
RS53V80-E	3	208-230-460	80 Gallon Vertical	Elite	32	24	76	16	8
RS51H80	1	208-230	80 Gallon Horizontal	Basic	60	24	45	24	N/A
RS53H80	3	208-230-460	80 Gallon Horizontal	Basic	60	24	45	16	8
RS51H80-E	1	208-230	80 Gallon Horizontal	Elite	60	24	45	24	N/A
RS53H80-E	3	208-230-460	80 Gallon Horizontal	Elite	60	24	45	16	8

No Start Up Kit Required

See catalog for additional options



Compressed Air Systems

Simplicity. It's What We Do

www.compressed-air-systems.com

